

# DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

## ALM3230 Automatic Laminator



**Labor-free automation with feeding, laminating, and trimming at the touch of a button!**

- Heated rollers for crystal clear scratch-free laminations
- Adjustable trim for full encapsulation or precise flush cut
- Sits on a tabletop or optional stand
- Green Button Operation: touch the button and walk away for labor-free, fully trimmed and laminated sheets
- ASAP adhesive laminating films in 1.5, 3, and 5 mil, gloss, matte, and Elegant Silk Matte adheres to hard-to-laminate digitally printed sheets

Eliminate time-consuming, costly hand feeding and trimming in laminating with the new value priced ALM3230 lamination system!

[www.drylam.com](http://www.drylam.com) • P: 800-225-5644 • F: 800-654-8339  
251 Wedcor Avenue • Wabash, IN 46992

ALM3230 Automatic Laminator



SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

# ALM3230 Automatic Laminator

## Key Features:

- Small Foot Print – less than 4 sq. ft.
- Table Top or optional stand with locking roller casters
- 115 Volt, 15 amp service with economy mode
- Ultra quick warm up of less than 5 minutes
- Virtually Unattended Operation
- Digital Sheets sizes: 13"x19", 12"x18", 11"x17", 8.5"x11"
- Laminates copy paper up to 100lb cover stock
- Automatic two side lamination or short one side work
- Adjustable Automatic Flush or Sealed edge trim
- 1 year parts and labor warranty

## ALM Exclusive ASAP Roll Film

- Perfect for Digital Print technology
- Anti-static properties

## ALM Exclusive ASAP Roll Film

1.5mil, 12.6"x 984 ft  
3.0mil, 12.6"x 492 ft  
5.0mil, 12.6"x 328 ft  
1.2mil, 12.6"x 984 ft, One Side Nylon set (Gloss & Matte Versions)



## Model ALM 3230

<b>Laminating Speed</b>	Fixed speed at 40"/min.
<b>Temperature Range</b>	170-270°F
<b>Ultra Fast Warm-Up Time</b>	Approximately 5 minutes
<b>Film Thickness</b>	1.5, 3, and 5 mil
<b>Thickness of Objects</b>	20lb bond - 100lb cover
<b>Paper Feeding Capacity</b>	100 Sheets, Adjustable Paper Guide
<b>Applicable Sizes:</b>	

**Letter** Paper Size 8½"x 11"

**Tabloid** Paper Size 11"x 17"

**Digital Paper** Size 12"x 18"

**Digital Paper** Size 13"x 19"

## Trimming Methods Operation Panel

(2 modes) Flush trim or edge seal for all 4 sides of the print  
LCD display for start, stop, temperature, and trim settings, leading and trailing edge side cuts are adjustable

## Other Features

Laminated sheet counter, Film tension control, Roller gap lever, Paper thickness feeder adjustment lever

## Power Consumption

900W

## Power Supply

AC 120V (60Hz)

## Net Weight

Laminator 100 Lbs. Stand: 48.5 Lbs.

## Optional Accessories

Rolling Stand

[www.drylam.com](http://www.drylam.com) • P: 800-225-5644 • F: 800-654-8339  
251 Wedcor Avenue • Wabash, IN 46992